

POWDER FIRE EXTINGUISHERS

- Available in 1, 2, 3, 4, 6 and 9kg sizes
- 5-year warranty
- Kitemarked to BS EN 3
- 2, 6 and 9kg are MED approved
- UKCA/CE approved
- Spray nozzle
- Squeeze grip operation
- Corrosion resistant finish
- Internal polyethylene lining
- Removable pressure gauge
- Protective plastic base (except 1, 2 and 3kg)
- Fitted with safety pressure relief valve
- Complete with wall bracket (4,6 and 9kg)
- Complete with bracket (1 and 2kg)
- Complete with transport strap (3kg)



	TITANPSE0 3-01	TITANPSE0 3-02	TITANPSE0 3-05	TITANPSE0 3-06	TITANPSE0 3-03	TITANPSE0 3-04
Capacity	1kg	2kg	3kg	4kg	6kg	9kg
Fire rating	8A 55B/C	13A 89B/C	21A 113B/C	21A 113B/C	43A 233B/C	55A 233B/C
Extinguishing medium	ABC Powder	ABC Powder	ABC Powder	ABC Powder	ABC Powder	ABC Powder
Cylinder height	345mm	382mm	366mm	445mm	525mm	558mm
Diameter	83mm	103mm	123mm	140mm	150mm	183mm
Filled weight	2.15kg	3.75kg	5.20kg	7.05kg	9.90kg	13.25kg
Working pressure	14.00 bar	14.00 bar	13.50 bar	13.50 bar	15.00 bar	15.00 bar
Temperature range	-30°C- +60°C	-30°C- +60°C	-30°C- +60°C	-30°C- +60°C	-30°C- +60°C	-30°C- +60°C
Pressuring gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen

