

PRESTIGE FIRE EXTINGUISHERS

- High fire ratings
- Assembled in the UK
- Wide range of models and sizes
- 6ltr foam/water and 6kg powder available with coloured or all-black labels
- Supplied complete with wall mounting brackets and hose/horn as standard
- 5-year warranty if serviced in accordance with BS5306: Part 3



	TITANSS CO2	TITANSS CO2-5KG	TITANSS PSE05-02	TITANSS PSE05-01	TITANSS PSE06-00	TITANSS PSE06-01	TITANSS PSE06-02	TITANSS PSE06-03	TITANSS PSE03-01	TITANSS PSE03-02	TITANSS PSE03-03	TITANSS PSE03-04
Capacity	2kg	5kg	6ltr	9ltr	1ltr	2ltr	6ltr	9ltr	1kg	2kg	6kg	9kg
Fire rating	34B	70B	13A	13A	5A 21B	8A 55B	13A 144B	21A 233B	8A 34B/C	13A 70B/C	27A 144B/C	43A 223B/C
Extinguishing medium	CO2	CO2	Water	Water	AFFF (Foam)	AFFF (Foam)	AFFF (Foam)	AFFF (Foam)	ABC 40 Powder	ABC 40 Powder	ABC 40 Powder	ABC 40 Powder
Cylinder material	Polished aluminium	Polished aluminium	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Working pressure	N/A	N/A	13.50 bar	13.50 bar	13.50 bar	13.50 bar	13.50 bar	13.50 bar	13.50 bar	13.50 bar	13.50 bar	13.50 bar
Temperature range	-20°C- +60°C	-20°C- +60°C	+5°C- +60°C	+5°C- +60°C	+5°C- +60°C	+5°C- +60°C	+5°C- +60°C	+5°C- +60°C	-30°C- +60°C	-30°C- +60°C	-30°C- +60°C	-30°C- +60°C
Pressuring gas	N/A	N/A	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen